


COMMERCIAL LINE DC INVERTER CASSETTE

Split system air conditioners



	A	B	C	D	E	F	
	mm	mm	mm	mm	mm	mm	kg
CASSETTE 12 INVERTER	647	647	50	570	570	260	16,3
CASSETTE 20 INVERTER	647	647	50	570	570	260	16,3
CASSETTE 25 INVERTER	950	950	55	830	830	205	21,6
CASSETTE 38 INVERTER	950	950	55	830	830	245	27,2

	A	B	C	D	E	F	
	mm	mm	mm	mm	mm	mm	kg
CASSETTE 38T INVERTER	950	950	55	830	830	245	27,2
CASSETTE 50 INVERTER	950	950	55	830	830	287	29,3
CASSETTE 60 INVERTER	950	950	55	830	830	287	29,3

MODEL		COOLING POWER kW	THERMAL POWER kW	€
CASSETTE 12 DC INVERTER U.I.	cod. 63000015	3,51 (0,85÷4,11)	3,80 (0,47÷4,31)	1.065,00
OUTDOOR UNIT 12 DC INVERTER U.E.	cod. 63000016			1.092,00
CASSETTE 20 DC INVERTER U.I.	cod. 63000017	5,27 (2,90÷5,59)	5,57 (2,37÷6,10)	1.194,00
OUTDOOR UNIT 20 DC INVERTER U.E.	cod. 63000018			1.520,00
CASSETTE 25 DC INVERTER U.I.	cod. 63000019	7,03 (3,30÷7,91)	7,62 (2,81÷8,94)	1.374,00
OUTDOOR UNIT 25 DC INVERTER U.E.	cod. 63000020			1.930,00
CASSETTE 38M FASE DC INVERTER U.I.	cod. 63000021	10,55 (2,70÷11,43)	11,14 (2,78÷12,30)	1.568,00
OUTDOOR UNIT 38M FASE DC INVERTER U.E.	cod. 63000022			3.249,00
CASSETTE 38T FASE DC INVERTER U.I.	cod. 63000021	10,01 (2,70÷11,43)	11,14 (2,78÷12,30)	1.568,00
OUTDOOR UNIT 38T FASE DC INVERTER U.E.	cod. 63000023			3.302,00
CASSETTE 50 DC INVERTER U.I.	cod. 63000024	14,07 (3,52÷15,83)	16,12 (4,10÷17,29)	1.714,00
OUTDOOR UNIT 50 DC INVERTER U.E.	cod. 63000025			3.876,00
CASSETTE 60 DC INVERTER U.I.	cod. 63000026	15,24 (4,10÷16,71)	18,17 (4,40÷19,93)	1.905,00
OUTDOOR UNIT 60 DC INVERTER U.E.	cod. 63000027			4.374,00

TECHNICAL DATA	UM	CASSETTE 12	CASSETTE 20	CASSETTE 25	CASSETTE 38M	CASSETTE 38T	CASSETTE 50	CASSETTE 60
Cooling power	kW	3,51 (0,85÷4,1)	5,27 (2,90÷5,59)	7,03 (3,30÷7,91)	10,55 (2,70÷11,43)	10,01 (2,70÷11,43)	14,07 (3,52÷15,83)	15,24 (4,10÷16,71)
Absorbed power*	kW	1,01	1,63	2,32	3,95	3,04	4,65	5,00
Current consumption*	A	4,45	7,20	10,20	17,50	6,5	8,10	8,60
S.E.E.R.		6,6 A++	6,3 A++	6,2 A++	6,7 A++	6,7 A++	6,1 A++	6,3 A++
Thermal power	kW	3,80 (0,47÷4,31)	5,57 (2,37÷6,10)	7,62 (2,81÷8,94)	11,14 (2,78÷12,30)	11,14 (2,78÷12,30)	16,20 (4,10÷17,29)	18,17 (4,40÷19,93)
Absorbed power*	kW	1,01	1,54	1,90	3,00	3,00	4,13	5,55
Current consumption*	A	4,73	6,8	8,50	13,50	5,0	8,00	9,60
S.C.O.P. Mid-range		4,1 A+	4,0 A+	4,0 A+	4,0 A+	4,0 A+	4,0 A+	4,0 A+
S.C.O.P. Warm-range		5,1 A+++	4,8 A+++	5,1 A+++	5,1 A+++	5,1 A+++	5,0 A+++	5,1 A+++
Power supply		230V/1/50Hz	230V/1/50Hz	230V/1/50Hz	230V/1/50Hz	380V/3+N/50Hz	380V/3+N/50Hz	380V/3+N/50Hz
Air flow	m ³ /h	620/510/420	720/620/500	1300/1140/1000	1700/1550/1380	1700/1550/1380	1970/1780/1580	2000/1850/1650
Sound level I.U.	dB (A)	42/37,5/34,5	45,4/44/39	45,5/47,5/42	51/49/46	51/49/46	52,5/50,5/48	54,5/52/49,5
Length Piping	m	≤ 25	≤ 30	≤ 50	≤ 75	≤ 75	≤ 75	≤ 75
Dislevel units	m	≤ 10	≤ 20	≤ 25	≤ 30	≤ 30	≤ 30	≤ 30
Gas connections		3/8"	1/2"	5/8"	5/8"	5/8"	5/8"	5/8"
Liquid connections		1/4"	1/4"	3/8"	3/8"	3/8"	3/8"	3/8"

* Value referred to the sum of the external unit + internal unit absorptions (separate power supplies)

Cooling test conditions: int. 27 ° C d.b. / 19.5 ° C wb. - Ext. 35 ° C d.b. / 24 ° C wb.

Heating test conditions: int. 20 ° C db. - Ext. 7 ° C d.b. / 6 ° C wb.

COMMERCIAL LINE - DUCTABLE ACCESSORIES DC INVERTER

Split system air conditioners

€



Multifunction wired remote control with follow me function, internal receiver and addressing

cod. 63000071

168,00



Wi-Fi control via smartphone or pad for R32 commercial series indoor units. App suitable for Android and iOS systems with all basic functions. Senior function, weekly timer, personalized sleep curve and self-control.

cod. 63000012

164,00



TWIN system kit, conversion from commercial range into dual split air conditioner

cod. 63000072

194,00



FLEX PIPE IN INSULATED PVC for ducts of 10 m - Ø 200

cod. 37900001

208,00



BRAGA to Y

cod. 65500020

50,00



DELIVERY PORT
40x20 cm with adjustable blades complete with damper

cod. 37900070

98,00



CONNECTION PLENUM Ø 200
40x20 cm between flex tube and delivery nozzle

cod. 37900019

146,00



ANCHOR BRACKETS FOR OUTDOOR UNITS
for mod. 9 - 12 complete with anti-vibration kit
for mod. 18 - 20 - 25 - 38 - 50 - 60 complete with anti-vibration kit

cod. 37081060


50,00

cod. 37081061

90,00



CIRCULAR DIFFUSERS Ø 200
with millimetrically adjustable cones and butterfly calibration damper



cod. 37900027

122,00



PLENUM CONNECTION Ø 200
between flexible tube and circular diffuser with adjustable cones



cod. 379000031

210,00